

# SL800 GNSS Receiver

Data Specifications

## GNSS

### Signal Tracking

GPS (L1C/A, L1C, L2C, L2P, L5)  
 GLONASS<sup>1</sup> (L1C/A, L2C/A, L2P, L3, L5)  
 BeiDou<sup>2</sup> (B1, B2, B3)  
 Galileo<sup>3</sup> (E1, E5 AltBOC, E5a, E5b, E6)  
 IRNSS (L5)  
 QZSS (L1C/A, L1C, L2C, L5, L6)  
 SBAS L1, L5, (WAAS, EGNOS, MSAS, GAGAN)  
 L-Band (Up to 5 Channels) TerraStar®

No. of Channels

555

## MEASUREMENT PERFORMANCE

Real-time Kinematic  
 Post Processing Kinematic  
 High-Precision Static  
 Static and Fast Static  
 DGPS Position Accuracy  
 SBAS Position Accuracy  
 Code Differential  
 Initializing Time  
 Initializing Reliability

H: 8mm + 1ppm RMS / V: 15mm + 1ppm RMS  
 H:8mm + 1ppm RMS / V:15mm + 1ppm RMS  
 H: 2.5mm + 0.1ppm RMS / V: 3.5mm + 0.4ppm RMS  
 H: 2.5mm + 0.5ppm RMS / V: 5mm + 0.5ppm RMS  
 H: 25cm RMS / V: 50cm RMS  
 H: 50cm RMS / V: 85cm RMS  
 DGPS/RTCM  
 <10s  
 99.9%

## COMMUNICATIONS

### Communication Ports

USB and RS232 serial port  
 Bluetooth 4.0, NFC  
 DC External power input  
 LED indicator panels

## SYSTEM

Operation System  
 Start-up Time  
 Data Storage

Linux  
 3s  
 8GB internal storage

## DATA MANAGEMENT

VRS, FKP, MAC, intRTK Support  
 NMEA and NovAtel ASCII Navigation Output  
 5 Hz Update (up to 100 Hz<sup>4</sup>)  
 RTCM 2.1, 2.3, 3.0, 3.1, 3.2  
 CMR, RTCA and NOVATELX

## GENERAL

### Environmental

IP67 environmental protection  
 Waterproof to 2m (6.5ft) depth  
 Temporary Submersion  
 Shock resistant body to 2m (6.5ft) pole drop  
 Temperature -40°C to 65°C Operating  
 -40°C to 75°C Storage

### Physical Properties

Size: 127.5mm x 57mm  
 Weight: 700g including battery  
 Power: 6 – 28V DC Input  
 Battery: 6300 mAh Li-Ion Battery  
 Battery Life: 9 hours (Static Measurement /  
 RTK Rover)

Note

<sup>1</sup> Hardware ready for L3 and L5  
<sup>2</sup> Designed for BeiDou phase 2 and 3, B1 and B2 compatibility. B3 conditionally supported and subject to change.  
<sup>3</sup> E1bc support only. Hardware ready for E6bc  
<sup>4</sup> Optional

# SL800

## GNSS Receiver



Satlab SL800 offers the flexibility to choose between either NFC or Bluetooth devices to best meet your surveying needs. Powered by the multi-constellation, triple frequency, long-range Bluetooth and Satlab Cloud Services support, this is the most convenient and efficient receiver for today's network age.

- Swedish Quality
- Multi-Constellation Tracking
- Bluetooth
- Long Battery Life (> 8 hours)
- Windows Compatibility
- Android Compatibility
- iOS Compatibility
- NFC Module
- Internet RTK Technology
- Lightweight

### The world's smallest GNSS receiver

The SL800 provides an easy solution for survey professionals who require a portable instrument to collect highly accurate data for various geospatial usage. Its portability feature allows user flexibility to easily collect data with just one receiver in the field connecting to CORS via any preferred devices to keep you focused and productive.



### Applications

- Mapping
- Land Survey
- Topography and As-built
- Landfill
- Hydrographic
- Agriculture
- Sensor
- UAV Base Station

### Efficient and dependable

Powered by NovAtel OEM729 GNSS engine, this receiver offers precise positioning and advanced interference mitigation which performs even in the most remote or challenging environments. Using its 555 channel tracking capabilities, it is able to track all current and upcoming signals, offering sub-metre to centimetre precise positioning.

### Satellite correction service

The SL800 has TerraStar capabilities that use a global network of multi-GNSS reference stations and advanced algorithms to generate highly precise GNSS satellite orbit, clock, biases, and other system parameters. These data allow TerraStar to provide correction services with sub-metre or centimetre-level positioning accuracy to SL800 receivers. Get your corrections transmitted in real-time, with minimal latency via satellites and cellular networks worldwide.

### TECHNICAL SUPPORT

Satlab offers online resources and a professional support network available worldwide.



- Multi-Constellation Tracking
- NFC Technology
- Data Collector
- Long Battery Life
- Professional Support Network