



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352 Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

APX-15 UAV

VERSION 3, SINGLE BOARD GNSS-INERTIAL SOLUTION

The Trimble APX-15 UAV is a GNSS-Inertial OEM solution designed to reduce the cost and improve the efficiency of mapping from small Unmanned Aerial Vehicles (UAVs). Comprised of a small single OEM board containing a precision GNSS receiver and inertial sensor components plus post-mission Differential GNSS-Inertial office software, the Trimble APX15 UAV eliminates the need to survey extensive Ground Control Points (GCP's), and reduces the amount of sidelap required to be flown, thus increasing the area flown per mission.

HIGH ACCURACY, EXTREMELY SMALL PACKAGE

Measuring just $60 \times 67 \text{ mm}$ and weighing only 60 grams, the Applanix APX-15 UAV provides unparalleled performance in an extremely small package. And with the included POSPac UAV post-mission software, it produces a highly accurate position and orientation solution for direct georeferencing of cameras, LIDARs and other UAS sensors.

THE APX-15 UAV BRINGS ALL THE BENEFITS OF DIRECT GEOREFERENCING TO UAV PLATFORMS:

- Turn your UAV into a professional mapping solution
- Ultra-fast image georeferencing for faster map production and delivery
- Reduced number of ground control points, saving time and money
- Consistent, reliable, highly accurate results
- Increased collection area per flight for greater productivity
- Redundant navigation solution to autopilot for enhanced safety

Key Features

- High-performance Direct Georeferencing solution for improved efficiency and accuracy of mapping from small Unmanned Aerial Vehicles
 - Reduce/eliminate GCP's
 - Reduce sidelap
 - Accurate LIDAR georeferencing
- Compact single-board OEM module complete with survey-grade multifrequency GNSS receiver and MEMS inertial components
- ► Applanix IN-FusionTM GNSS-Inertial and SmartCalTM compensation technology
- POSPac UAV Differential GNSS Inertial post-processing software for highest accuracy
- RTK real-time position for precision landing applications
- Supports all common RTK corrections such as CMR, CMR+, RTCM





APX-15 UAV

TECHNICAL SPECIFICATIONS

System Summary

- Advanced Applanix IN-Fusion™GNSS-Inertial integration technology
- Solid-state MEMS inertial sensors with Applanix SmartCal™ compensation
- · Advanced Trimble Maxwell Custom GNSS survey technology
- · 336 Channels
 - GPS: L1 C/A, L2C, L2E, L5
 - GLONASS: L1 C/A, L2 C/A, L3 CDMA8
 - BeiDou: B1, B2
 - Galileo1: E1, E5A, E5B, E5AltBOC
 - QZSS: L1 C/A, L1 SAIF, L1C, L2C, L5, LEX
 - SBAS: L1 C/A, L5
 - MSS L-band: Trimble RTX, OmniSTAR
- · High precision multiple correlator for GNSS pseudorange measurements Unfiltered, unsmoothed pseudorange measurements data for low noise, low
- multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- 100 Hz position, roll, pitch and heading output
- · Generic Gimbal and Autopilot support
- IMU data rate 200 Hz
- Navigation output format: ASCII (NMEA-0183), Binary (Trimble GSOF)
 Supported Reference input: CMR, CMR+, sCMRx, RTCM 2.1, 2.2, 2.3, 3.0, 3.1
- Support for POSPac UAV post-processing software (included)
- · No export permit required

LAN INPUT/OUTPUT

All Ethernet functions are supported through dedicated IP address (Static or DNS) simultaneously.

TCP/IP and UDP ASCII and Binary data streaming (Time tag, PPS sync, status,

position, attitude, velocity, track and speed, dynamics,

performance metrics, GNSS data)

HTTP Web based Control software (GUI) for easy system

configuration and low rate display. Support for all common browsers (IE, Safari, Mozilla, Google Chrome, Firefox)

SERIAL INPUT/OUTPUT

RS232 level port TTL level (3.3 V) port

Parameters

ASCII and Binary data streaming (Time tag, PPS sync, status, position, attitude, velocity, track and speed, dynamics, performance metrics, GNSS data), reference input (CMR CMR+, sCMRx, RTCM), configuration messages, Gimabal Encoder and Autopilot input support.

OTHER INPUT/OUTPUT

PPS (pulse-per-second) Time Sync Pulse output

Event Input (2) Two time mark of external events

TTL 3.3 V pulses, max rate 50 Hz

Digital I/O (3) LED drivers with dedicated functionality for systems integrators

- Developed under a License of the European Union and the European Space Agency
- Typical performance. Actual results are dependent upon satellite configuration, atmospheric conditions and other environmental effects
 Typical survey mission profile, max RMS error. Heading error will increase for low speed rotor applications and
- when hovering.
- Requires base station and radio link, sold separately
- POSPac UAV, short base line operation Sensor bandwidth (-3 dB amplitude) ~ 50 Hz
- Sold separately
- 8 There is no official GLONASS L3CDMA or Galileo E6 ICD. The current tracking capability is based on publicly available information. Full receiver compatibility cannot be guaranteed

LOGGING

Internal Logging 6 GByte Flash memory External Logging USB 2.0 Device port

Parameters Time tag, status, position, attitude, velocity, track and speed,

+++++++++++++++++++++

dynamics, performance metrics, raw IMU data (200 Hz), raw

++++++++++++++++

GNSS data (5 Hz)

PERFORMANCE SPECIFICATIONS² (RMS ERROR)

Unmanned Airborne Vehicle Applications

	SPS	DGPS	RTK⁴	Post-Processed⁵
Position (m)	1.5 - 3.0	0.5 - 2.0	0.02 - 0.05	0.02 - 0.05
Velocity (m/s)	0.05	0.05	0.02	0.015
Roll & Pitch (deg)	0.04	0.03	0.03	0.025
True Heading ³ (deg)	0.30	0.28	0.18	0.080

PHYSICAL CHARACTERISTICS

Size	
Weight	
Power	
	consumption of 3.5W at room temperature
Connectors	
	(mating part FCI 90311-044LF)
Antenna Port:	
	Output Voltage: 3.3 V DC to 5 V DC
	Maximum Current: 400 mA
	Minimum Input Signal Strength: 32 dB

ENVIRONMENTAL CHARACTERISTICS

Temperature:	40 deg C to +75 deg C (Operational)
	-55 deg C to +85 deg C (Storage)
Measurement Range:	+/- 6g ⁶ , +/- 300 dps
Mechanical Shock:	+/- 75g Survival
Operating Humidity:.	5% to 95% R.H. non-condensing at +60 deg C
Maximum Operating Limits.	515 m/sec
	18 000 m

ADDITIONAL ACCESSORIES7

Evaluation Kit (Development Board)

POSPAC UAV OFFICE SOFTWARE

- Post-processed Differential GNSS-Inertial SW for APX-15
- 200 Hz Navigation solution (Position, Velocity, Orientation, Rates, Accelerations)
- Applanix IN-Fusion GNSS-Integration technology
- Full support for UAV dynamic models
- Single Base Differential GNSS-Inertial processing
- Forward and reverse processing with optimal Smoother
- Support for Applanix SmartBase virtual reference station module⁷

Specifications subject to change without notice



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352 Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

