

BROADCAST BANDS



All catalog part numbers are for devices with clockwise rotation, however, counter-clockwise rotation is available by request. Encapsulation is available on some designs for high peak power and high altitude capability. Contact our Customer Service Department for special performance and unique mechanical configurations. We have many other designs not listed here on our website as we develop new designs on a frequent basis.

F = Female Connector M = Male Connector

*** Case Temperature Not To Exceed Operating Temperature**

Coaxial Circulators - Broadcast Bands

Frequency Range (GHz)	Insertion Loss (Max) (-dB)	VSWR (Max)	Operating Temperature °C	Connector Configuration	F=Female M=Male	Power Rating (Watts)	Dimensions (in x in x in)	Part Number	Outline Drawing
0.470-0.518	0.30	1.20	0 to +65	DIN	FFF	700	2.75 x 2.94 x 1.26	994-038072-021	C04
0.470-0.548	0.30	1.20	0 to +65	N-Type	FFF	700	2.75 x 2.94 x 1.26	994-038072-025	C05
0.487-0.573	0.35	1.25	0 to +65	N-Type	FFF	700	2.75 x 2.94 x 1.26	995-487573-901	C05
0.518-0.596	0.30	1.20	0 to +65	DIN	FFF	700	2.75 x 2.94 x 1.26	994-038072-022	C04
0.542-0.656	0.30	1.20	0 to +65	N-Type	FFF	700	2.75 x 2.94 x 1.26	994-038072-026	C05
0.596-0.704	0.30	1.20	0 to +65	DIN	FFF	700	2.75 x 2.94 x 1.26	994-038072-023	C04

רח' אודם 14, ת.ד. 7042 פ"ת ▪ טל: 03-9243352 ▪ פקס: 03-9243358

www.hypertech.co.il ▪ sales@hypertech.co.il



0.650-0.806	0.30	1.20	0 to +65	N-Type	FFF	700	2.75 x 2.94 x 1.26	994- 038072- 027	C05
0.701-0.806	0.30	1.20	0 to +65	DIN	FFF	700	2.75 x 2.94 x 1.26	994- 038072- 024	C04
0.806-0.860	0.30	1.20	0 to +65	N-Type	FFF	700	2.75 x 2.94 x 1.26	994- 038072- 028	C05

רח' אודם 14, ת.ד. 7042 פ"ת ▪ טל: 03-9243352 ▪ פקס: 03-9243358

www.hypertech.co.il ▪ sales@hypertech.co.il

