



KEY FEATURES

220 Channels for multi-constellation GNSS support

Fully EMI shielded module

Compact design for mobile applications

Integrated Bluetooth™/Wi-Fi

Integrated 3.5G Cellular Modem

Flexible RS232, USB and Ethernet interfacing

Centimeter level position accuracy

Proven Trimble Maxwell 6 technology



BD920-W3G GNSS RECEIVER

DUAL FREQUENCY GPS/GLONASS RECEIVER WITH INTEGRATED COMMUNICATIONS SPEEDS DEVELOPMENT OF MOBILE POSITIONING APPLICATIONS

THE LATEST IN GNSS TECHNOLOGY FROM TRIMBLE IS NOW AVAILABLE TO ORIGINAL EQUIPMENT MANUFACTURERS (OEM) AND SYSTEM INTEGRATORS.

GNSS AND COMMUNICATION TIGHT INTEGRATION

The Trimble® BD920-W3G module has been designed for applications requiring centimeter accuracy in a compact package. By integrating wireless communications on the same module the task of receiving and transmitting data such as RTK corrections is greatly simplified. A single intuitive web interface allows a variety of use cases to be supported. In addition to GNSS base and rover setups with Wi-Fi or UMTS modem the module also allows simultaneous customer access to the internet.

Both GNSS and communication components are fully shielded. This design ensures the high quality signals are protected from the sources of EMI on the host platform. It also significantly reduces radiated emissions which speeds compliance certification and time to market.

MULTI CONSTELLATION GNSS

The Trimble BD920-W3G supports both L1 and L2 frequencies from the GPS and GLONASS constellations plus the E1 frequency from Galileo. This delivers the quickest and most reliable RTK initializations for 1–2 centimeter positioning. For applications that do not require centimeter accuracy the BD920-W3G contains an advanced kalman filter PVT engine that delivers high accuracy GNSS, DGNSS or SBAS positions in the most challenging environments such as urban canyons. Different configurations of the module are available including single frequency RTK and GPS only. All features are password-upgradeable, allowing functionality to be upgraded as your requirements change.

The receiver also supports Fault Detection and Exclusion (FDE) and Receiver Autonomous Integrity Monitoring (RAIM) for safety-critical applications.

DEMONSTRATED PERFORMANCE

Industry professionals trust Trimble embedded positioning technologies as the core of their precision applications. With the latest Trimble-precise Maxwell™ 6 technology, the BD920-W3G provides assurance of long-term future-proofing and trouble-free operation. Moving the industry forward, the Trimble BD920-W3G redefines high-performance positioning:

- On-board multipath mitigation
- Proven low-elevation tracking technology
- Dramatically improved RTK Initialization

FLEXIBLE INTERFACING

The Trimble BD920-W3G was designed for easy integration and rugged dependability. Customers benefit from the Ethernet connectivity available on the board, allowing high speed data transfer and configuration via standard web browsers. USB and RS-232 are also supported. Just like other Trimble embedded technologies, easy to use software commands simplify integration and reduce development times.

TRIMBLE BD920-W3G GNSS RECEIVER MODULE/COMMUNICATION MODULE

TECHNICAL SPECIFICATIONS¹

- 220 Channels:
 - GPS: L1 C/A, L2E, L2C
 - GLONASS: L1 and L2 C/A
 - Galileo: E1²
 - QZSS: L1 C/A, L1 SAIF, L2C
 - SBAS: L1 C/A
- High precision multiple correlator for GNSS pseudorange measurements
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- Up to 20 Hz raw measurement & position outputs
- Reference outputs/inputsCMR, CMR+, sCMRx, RTCM 2.1, 2.2, 2.3, 3.0, 3.1¹³
- Navigation outputs ASCII: NMEA-0183 GSV, AVR, RMC, HDT, VGK, VHD, ROT, GGK, GGA, GSA, ZDA, VTG, GST, PJT, PJK, BPQ, GLL, GRS, GBS and Binary: Trimble GSOFF
- 1 Pulse Per Second Output
- Event Marker Input Support
- Supports Fault Detection & Exclusion (FDE), Receiver Autonomous Integrity Monitoring (RAIM)

COMMUNICATION SPECIFICATIONS

- 1 USB 2.0 Device port
- 1 LAN Ethernet port:
 - Supports links to 10BaseT/100BaseT auto-negotiate networks
 - All functions are performed through a single IP address simultaneously—including web GUI access and raw data streaming
 - Network Protocols supported
 - ▶ HTTP (web GUI)
 - ▶ NTP Server
 - ▶ NMEA, GSOFF, CMR over TCP/IP or UDP
 - ▶ NTripCaster, NTripServer, NTripClient
 - ▶ mDNS/uPnP Service discovery
 - ▶ Dynamic DNS
 - ▶ eMail alerts
 - ▶ Network link to Google Earth
 - ▶ Support for external modems via PPP
- 3 x RS232 ports
 - Baud rates up to 115,200
- Control Software: HTML web browser, Internet Explorer, Firefox, Safari, Opera, Google Chrome
- Integrated 802.11 a/g/b Wi-Fi wireless technology. Client or access point
- Integrated 2.4 GHz Bluetooth V3.0 wireless technology¹²
- Optional Integrated 3.5G UMTS data module supporting WCDMA and HSDPA

POSITIONING SPECIFICATIONS⁴

Mode	Accuracy ⁴	Latency ⁵	Maximum Rate
Single Baseline RTK (<30 km)	0.008 m + 1 ppm Horizontal	<20 ms	20 Hz
	0.015 m + 1 ppm Vertical		
DGNSS	0.25 m + 1 ppm Horizontal	<20 ms	20 Hz
	0.50 m + 1 ppm Vertical		
SBAS ⁷	0.50 m Horizontal	<20 ms	20 Hz
	0.85 m Vertical		

RTK initialization time³ typically <10 seconds
 RTK initialization reliability³ >99.9%

PERFORMANCE SPECIFICATIONS

Time to First Fix (TTFF) ⁷	
Cold Start ⁸	<45 seconds
Warm Start ⁹	<30 seconds
Signal Re-acquisition	<2 seconds
Velocity Accuracy ^{3,4}	
Horizontal	0.007 m/sec
Vertical	0.020 m/sec
Acceleration	11 g
Maximum Operating Limits ¹⁰	
Velocity	515 m/sec
Altitude	18,000 m

PHYSICAL AND ELECTRICAL CHARACTERISTICS

Size60 mm x 55 mm x 19 mm
Power	5 V DC 28 V DC
	Typical 1.3 W (L1/L2 GPS + L1/L2 GLONASS)
Weight	54 grams
Connectors	
I/O	44 -pin header
GNSS Antenna	MMCX receptacle
Wi-Fi/Bluetooth antenna	MMCX receptacle
UMTS antenna	MMCX receptacle
Antenna LNA Power Input	
Input voltage	3.3 V DC to 5 V DC
Maximum current400 mA
Minimum required LNA Gain	28.5 dB

ENVIRONMENTAL CHARACTERISTICS¹⁰

Temperature	
Operating	-40 °C to +85 °C
Storage	-55 °C to +85 °C
Vibration	MIL810F, tailored
	Random 6.2 gRMS operating
	Random 8 gRMS survival
Mechanical shock	MIL810D
	±40 g operating
	±75 g survival
Operating Humidity	5% to 95% R.H. non-condensing, at +60 °C

ORDERING INFORMATION

Module Trimble BD920-W3G GNSS available in a variety of configurations from L1 SBAS upwards
 Evaluation Kit Includes interface board and power supply

1 Trimble BD920-W3G is available in a variety of software configurations. Specifications shown reflect full capability.
 2 Developed under a License of the European Union and the European Space Agency.
 3 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
 4 1 sigma level, when using Trimble Zephyr 2 antennas.
 5 At maximum output rate.
 6 GPS only and depends on SBAS System performance. FAA WAAS accuracy specifications are <5 m 3DRMS.
 7 Typical observed values.
 8 No previous satellite (ephemerides / almanac) or position (approximate position or time) information.
 9 Ephemerides and last used position known
 10 As required by the U.S. Department of Commerce to comply with export licensing restrictions.
 11 Dependent on appropriate mounting/enclosure design.
 12 Bluetooth type approvals are country specific
 13 Input only network correction

Specifications subject to change without notice.

© 2014, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell is a trademark of Trimble Navigation Limited. All other trademarks are the property of their respective owners. 11/2014