



# Thunderbolt PTP GM200

PTP Grandmaster designed for small cell, 4G and LTE-A deployments



## Thunderbolt GMC GM200 Grandmaster Clock

The Trimble Thunderbolt® PTP Grandmaster Clock is designed for wireless networks requiring phase synchronization. The GM200 provides continuous availability of UTC traceable time for phase synchronization, a must for LTE-Advanced networks and services..

The Thunderbolt PTP GM200 employs industry leading Trimble GNSS solution & holdover technology.

The PTP GM200 can tolerate harsh environmental conditions supporting both indoors & outdoors deployments with extended operating temperature range.

### Small cell phase synchronization

The Thunderbolt PTP GM200 is designed with small cells in mind but also it meets Marco base station requirements for synchronization.

The Thunderbolt PTP GM200 supports small cells networks that require phase synchronization. The most efficient way to implement phase synchronization for LTE & LTE-A services is to deploy the grandmaster clock close to target eNodeBs to ensure 1.5 us of phase alignment.

By reducing network hops between the grandmaster and eNodeBs, the risk

of network re configuration and load variance on IEEE-1588 signal quality is reduced. The Trimble GM200 suits this strategy perfectly due to its small size, low cost, superior accuracy & reliability and flexibility of deployment options.

### Ideal for LTE A services

CoMP, eCIC, eMBMS and Carrier Aggregation services require that synchronization networks be requalified and redesigned to support phase synchronization. Non-compliance with phase sync specifications will result in low or no service from LTE-A equipment and degraded bandwidth leading to potential service outages.

By engineering current networks to support phase synchronization, LTE A services downtime can be mitigated. Phase synchronization can easily be supported by current sync networks with the GM200 by adding it where needed. Given its low cost, it can be added to any network requiring support for the stringent phase synchronization specifications that LTE-A services require performing at their optimal levels.

NEBS compliance assures that the GM200 can be deployed in edge and/or aggregation networks.

## Key Features

- IEEE-1588 PTP Grandmaster Clock
  - Multiple PTP Profiles (G.8265.1, G.8275.1, G.8275.2, Telecom-2008 Profile)
  - Supports 64 PTP clients
- Multi-Constellation (GPS, GLONASS, BDS & Galileo)
- 15ns time accuracy relative to GPS reference
- Holdover of  $\pm 1.5\mu s$  over 4hours (constant temperature and when locked to GPS for 7 days)
- Inputs: GNSS, 1588-PTP and SyncE
- Outputs: 1588-PTP, NTP, SyncE, PPS, and 10MHz
- Dedicated management port (1xRJ45)
- Network Management: SNMP, Web UI, CLI
- VLAN support
- IPv4 and IPv6

## Benefits

- Low cost reduces CAPEX of LTE TDD, LTE A & small cell projects
- Extended environmental capabilities enable deployment in difficult locations where small cells and LTE A base stations are deployed
- Superior holdover performance via Trimble proprietary technology gives extra time error budget for network design and dimensioning.



14 Odem ST. P.O.B. 7042 Petach Tikva 497001, ISRAEL | Office: +972-3-924-3352  
Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il



## GENERAL SPECIFICATIONS

Inputs.....GNSS (GPS, GLONASS, Beidou & Galileo)  
1588-PTP, SyncE  
Outputs.....Ethernet: 1x Mgmt RJ45  
2x SFP  
Protocols.....PTP, NTP & SyncE  
GNSS Antenna .....SMA

Protocols:  
IEEE-1588 (PTP), NTPv4, SyncE, IPv4, IPv6, Telnet, SFTP,  
SSH, RADIUS, SNMP

Network Management.....SNMPv2, HTTPS, CLI

User Interfaces:  
CLI.....Monitoring and Management  
Web UI.....Monitoring and Management

## PERFORMANCE

Time of day accuracy.....15ns (1-sigma) from UTC  
Time stamp accuracy.....<10 ns rms  
Frequency accuracy..... $1.16 \times 10^{-12}$  (one day ave.)  
Holdover..... $<1 \times 10^{-10}$  /24hrs

Time accuracy  
Tracking to GPS.....<15ns (locked)  
Holdover..... $\pm 1.5 \mu\text{s}$ /4hrs (7 days locked)

PTP GM configuration.....64 clients @128 mps  
Surveyed accuracy.....<3m Horizontal, <5m Vertical  
Power consumption.....5W average, 10W maximum

## PHYSICAL CHARACTERISTICS

Dimensions in cm (L x W x H):.....20.8 x 20 x 4.4  
(19" half-rack x 1U)  
Weight.....< 3Kg (6 lb)

## POWER

DC Power, dual feed.....-36VDC to -72VDC  
Power-over-Ethernet (POE).....Optional

## REGULATORY & STANDARDS

Operating Conditions  
Temperature.....-40°C to +85°C  
Humidity.....5%-95% RH non-condensing (+60°C)  
Storage Temperature.....-55°C to +105°C

Safety & Environmental:  
UL / CSA 60950-1  
EN: 60950-1, 300019  
CE, CISPR22 class A  
GR-63; Level 3  
ETSI (EN55022/EN55024) EN 300019, Class T3.2

Electrical.....EMC, ESD Immunity & susceptibility  
FCC Part 15 Class A  
EN.....300 386, 55022 class A, 55024, 61000-6-2/4  
IEEE.....1613-1  
Telcordia.....GR-1089

Synchronization  
ITU.....G.8265.x, G.8275.x (PRTC/T-GM)  
IEEE.....PTP (IEEE 1588v2)  
IETF.....NTPv4 (RFC5905)

Environmental  
RoHS-II & WEEE Compliant

*Parts of the product are patent protected.*

*Trimble has relied on representations made by its suppliers in certifying this product as RoHS-II compliant.*

*Specifications are subject to change without notice.*

*Trimble Navigation Limited is not responsible for the operation or failure of operation of GPS satellites or the availability of GPS satellite signal.*