








High Performance Telecom Discrete OCXO

► APPLICATIONS: IEEE 1588 (G.8283, G.8273.x), SyncE and Stratum 3E modules, Time and frequency reference, Test equipment, Wireless and LTE-TDD Base Stations, Carrier Networking.

MODEL	IMAGE	PACKAGE	FREQUENCY RANGE	FREQUENCY STABILITY	24 HOUR HOLDOVER (CONSTANT TEMP)	RETRACE AT 25°C
ROX3827T3 <i>New</i>		38.1 x 27.1 x 11.7 mm 38.1 x 27.1 x 17 mm	5 - 40 MHz	1 ppb pk-pk (-40 to 85 °C)	<13 µs (H = 11.7 mm) <5 µs (H = 17 mm)	±5 ppb
ROX3627T3		36.5 x 27 x 13.7 mm 36.5 x 27 x 19 mm	5 - 40 MHz	±5 - 10 ppb (-40 to 85 °C)	<13 µs (H = 13.7 mm) <5 µs (H = 19 mm)	±5 ppb
ROX2525T5		25.4 x 25.4 x 11.5 mm 25.4 x 25.4 x 12.7 mm	10 - 66 MHz	±5 - 10 ppb (-40 to 85 °C)	<25 µs	±5 ppb
ROX2525S4 <i>New</i>		25 x 25 x 15.24 mm	10 - 40 MHz	±5 - 10 ppb (-40 to 85 °C)	<25 µs	±5 ppb
ROX2522S4		25 x 22 x 11.5 mm 25 x 22 x 15.2 mm	10 - 40 MHz	±5 - 10 ppb (-40 to 85 °C)	<25 µs	±5 ppb



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352
 Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

