







High Stability TCXO

► **APPLICATIONS:** Smart Wireless Devices, Communications, Consumer Products, LBS Handset, PCMCIA CDPD cards, PDA, PND, WIMAX/WLAN, Wi-Fi and GNSS applications.

MODEL	IMAGE	PACKAGE	FREQUENCY RANGE	STABILITY (FVST)	OUTPUT	FEATURES
IT2100F		2.0 x 1.6 mm	13 - 52 MHz	±0.5 - 2 ppm (-40 to 85 °C)	Clipped sinewave	4 pin 3.3 - 1.8 V
IT2200K		2.5 x 2.0 mm	10 - 52 MHz	±0.5 - 2.5 ppm (-40 to 85 °C)	Clipped sinewave	6 pin 3.3 - 1.8 V
IT2200J		2.5 x 2.0 mm	10 - 52 MHz	±0.5 - 2.5 ppm (-40 to 85 °C)	Clipped sinewave	4 pin 3.3 - 1.8 V
IT3200C		3.2 x 2.5 mm	10 - 40 MHz	±0.5 - 5 ppm (-40 to 85 °C)	Clipped sinewave	6 pin 3.7 - 2.4 V



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352
Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il