

COMMUNITHINGS SENSOR DATASHEET

CommuniThings provides rich smartparking solutions including sensors, dashboard, steward interface and mobile app.





COMMUNITHINGS Sensor - Specifications

Key Features

- Triple detection technology
- Bi-directional communication between sensor and user through mobile app or smart-tag
- High protection against mechanical and chemical influences
- Dashboard alarm in case of failing sensor
- 5 to 7 years field replaceable battery life
- LoRa, LoRaWAN, NB-IoT compliant

Detection

- Triple detection technology ultrasound, infrared, magnetic
- Better than 98 % detection

Installation

Flush mounted

Communication

- LoRa, LoRaWAN, NB-IoT
- 868 Mhz (EU), 902-928 MHZ (US), AS923 and AU915 (Aus, NZ)
- Wireless Software updates

Battery Life Time

- Replaceable Lithium Battery
- 5 7 years under normal traffic usage

Mechanical and environmental properties

- Anti-vandalism
- Load resistance : heavy traffic
- Protection grade : IP68
- Resistance to mechanical influences from vertical and horizontal forces: heavy vehicles/trucks, snow plough with variable force
- Resistance to chemical influences: oil, fuel, salt for snow removal
- Alarming on dashboard in case of sensor failing
- Humidity range: 0 to 95%
- Operating temperature : 40°C to + 85°C

Various

- Size base Ø: 120 mm Top Ø: 140 mm
- Color Black
- Material: PA with high resistance and rigidity characteristics
- 1024 kb EEPROM

