

# Trimble BD1092i

Dual antenna receiver module with integrated inertial navigation system for industrial applications

## Precise positioning and orientation

The Trimble® BD1092i is a high accuracy, quad-band, dual-antenna GNSS/INS receiver module designed for applications requiring continuous centimeter level position and orientation accuracy in a board level package.

## Maxwell 8 technology

The Trimble BD1092i is built around a set of hardware and software innovations that are collectively known as Trimble Maxwell™ 8 technology. At the core of the technology is the Maxwell 8 baseband GNSS ASIC (application-specific integrated circuit). This is the 8th generation ASIC in the Maxwell family featuring an architecture engineered from the silicon level up to support the most advanced Trimble jammer anti-jamming mitigation. Trimble JammerGuard™ provides continuous high accuracy and reliable positioning by actively monitoring and mitigating unwanted interference across all GNSS frequency bands. L5 Assured™ enables L5-only startup during total L1 jamming, delivering reliable RTK/RTX positioning when L1 is unavailable.

Maxwell 8 technology also incorporates advanced spoofing innovations to detect and neutralize the growing threat of fraudulent GNSS signals. By identifying these sophisticated spoofing attacks, the system prevents the receiver from calculating erroneous positions that could otherwise deviate by significant distance. The architecture leverages Trimble RTX®-NMA and Galileo OSNMA for real-time authentication of broadcast GNSS ephemeris data.

## Trimble ProPoint engine

Driven by a high-performance quad-core processor, the field-proven Trimble ProPoint® positioning engine delivers accuracy, availability and integrity from the Maxwell 8 precision measurements. Tight fusion with onboard inertial sensors provides optimal performance during GNSS outages or degraded signal environments. Trimble IonoGuard™ Technology mitigates the effects of high ionospheric activity caused by solar storms, significantly increasing operational uptime. It also provides real-time diagnostics for each individual satellite for enhanced user awareness.

The Trimble ProPoint engine supports a variety of GNSS and GNSS/INS positioning modes. Depending on the availability of differential corrections (SBAS, DGNSS, RTK or RTX) the engine will gracefully transition positioning modes to deliver uninterrupted positioning and best available accuracy.

## Flexible Integration

Designed for embedded industrial applications, the compact BD1092i board allows flexible hardware and software integration. Ethernet support enables rapid data throughput and remote configuration via a standard web-browser interface. It also supports USB, CAN and RS-232 serial protocols for a wide range of hardware compatibility. An intuitive, interactive web GUI simplifies complex setup tasks, including the precise input of sensor lever arms.

## Key benefits

- Trimble Maxwell 8 technology
- 1400 channels for all available satellite signals
- Trimble JammerGuard jamming mitigation
- Spoofing protection including RTX-NMA and OSNMA
- Trimble ProPoint RTK/RTX positioning engine with IonoGuard
- Trimble EVEREST™ Plus Multipath mitigation
- High Accuracy MEMS inertial sensors for precise position and orientation
- 10x improvement in vibration sensitivity
- PTP high-precision timing support
- Advanced RF Spectrum® Analyzer toolkit
- Easy to integrate board form factor



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352  
Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

# Trimble BD1092i

Dual antenna receiver module with integrated inertial navigation system

## Technical specifications<sup>1</sup>

- Trimble Maxwell 8 technology
- Trimble JammerGuard Jamming mitigation
- Trimble ProPoint positioning engine
- Onboard Advanced MEMS inertial sensors
- Position Antenna based on 700 Channel Maxwell 8 chip:
  - GPS: L1 C/A, L1C, L2E, L2C, L5
  - BeiDou: B1, B2, B2A, B2B, B3
  - GLONASS: L1 C/A, L1P, L2 C/A, L2P, L3 CDMA
  - Galileo: E1, E5A, E5B, E5AltBOC, E6
  - IRNSS: L5
  - QZSS: L1 C/A, L1 SAIF, L1C, L2C, L5, LEX
  - SBAS: L1 C/A, L5
  - MSS L-Band: Trimble RTX
- Vector Antenna based on second 700 Channel Maxwell 8 chip:
  - GPS: L1 C/A, L2E, L2C, L5
  - BeiDou: B1, B2, B3
  - GLONASS: L1 C/A, L2 C/A, L3 CDMA
  - Galileo: E1, E5A, E5B, E5AltBOC, E6
  - IRNSS: L5
  - QZSS: L1 C/A, L1 SAIF, L1C, L2C, L5, LEX
- High precision multiple correlator for GNSS pseudorange measurements
- Trimble EVEREST Plus multipath mitigation
- Trimble RTX-NMA, Galileo OSNMA spoofing protection
- Supports Trimble CenterPoint® RTX, Trimble FieldPoint RTX and Trimble RangePoint® RTX<sup>10</sup>
- Galileo HAS and QZSS CLAS support
- Advanced RF Spectrum Monitoring and Analysis software
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Proven Trimble low elevation tracking technology
- Reference outputs/inputs:
  - CMR, CMR+™, sCMRx, RTCM 2.1, 2.2, 2.3, 3.0, 3.2, 3.3, 3.4 (MSM)
- Navigation Outputs:
  - ASCII: NMEA-0183
  - Binary: Trimble GSOE, NMEA2000
- 1 Pulse Per Second Output
- PTP high-precision timing protocol support
- Event marker input support
- Supports Fault Detection & Exclusion (FDE), Receiver Autonomous Integrity Monitoring (RAIM)

## Key features include:

- High update rate position and orientation solution
- Dual-antenna for instantaneous heading alignment
- Continuous positioning in GNSS denied environments
- Lever arm calculation from antenna to reference point of interest
- Patented anti-jamming and anti-spoofing technology
- Form, fit, and function compatible with BD99x modules

## Communication

- 1 USB 2.0 Device port
- 2 LAN Ethernet ports:
  - Supports links to 10BaseT/100BaseT auto-negotiate networks
  - All functions are performed through a single IP address simultaneously—including web GUI access and raw data streaming
  - Network Protocols supported:
    - HTTP (web GUI)
    - NMEA, GSOE, CMR over TCP/IP or UDP
    - NTripCaster, NTripServer, NTripClient
    - mDNS/uPnP Service discovery
    - Dynamic DNS
    - Email alerts on receiver status
    - Network link to Google Earth™ mapping system
    - Support for external modems via PPP
    - RNDIS Support
    - NTP, PTP
- 3 × RS232 ports:
  - Baud rates up to 921,600
- 1 CAN Port
- WebUI for configuration, status and data transfer
- ROS 1 and ROS 2 drivers available



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352  
 Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

# Trimble BD1092i

Dual antenna receiver module with integrated inertial navigation system

| Ordering information                        |                                                                          |
|---------------------------------------------|--------------------------------------------------------------------------|
| Module Number                               | 210923-XX                                                                |
| Upgrades                                    | Software options including: Accuracy level, Update rate, Heading and INS |
| Evaluation Kit                              | Includes interface board, power supply                                   |
| Performance specifications                  |                                                                          |
| Time to First Fix (TTFF) <sup>5</sup>       |                                                                          |
| Cold Start <sup>6</sup>                     | <45 seconds                                                              |
| Warm Start <sup>7</sup>                     | <30 seconds                                                              |
| Signal Re-acquisition                       | <2 seconds                                                               |
| Velocity accuracy <sup>2</sup>              |                                                                          |
| Horizontal                                  | 0.007 m/sec                                                              |
| Vertical                                    | 0.020 m/sec                                                              |
| Maximum acceleration GNSS tracking          |                                                                          |
|                                             | ±11 g                                                                    |
| Inertial sensors                            |                                                                          |
| Maximum acceleration                        | ±8 g                                                                     |
| Maximum angular rate                        | ±300 deg/sec                                                             |
| Maximum Operating Limits <sup>8</sup>       |                                                                          |
| Velocity                                    | 600 m/sec                                                                |
| Altitude                                    | 18,000 m                                                                 |
| Positioning                                 |                                                                          |
| RTK initialization time <sup>2</sup>        | typically <8 seconds                                                     |
| RTK initialization reliability <sup>2</sup> | <99.9 %                                                                  |
| Position latency <sup>3</sup>               | <20 ms                                                                   |
| Maximum position/ attitude update rate      | 100 Hz                                                                   |

| Physical and electrical characteristics    |                                                                          |
|--------------------------------------------|--------------------------------------------------------------------------|
| Size (L × H × D)                           | 100 mm × 60 mm × 11.6 mm                                                 |
| Power                                      | 3.3 VDC +5%/-3%, Typical 5.4 W (L1 GNSS)                                 |
| Weight                                     | 60 grams                                                                 |
| Connectors                                 |                                                                          |
| I/O                                        | 44-pin header, 14-pin socket, 10-pin socket                              |
| GNSS Antenna                               | 2 x MMCX receptacle                                                      |
| Antenna LNA Power Input                    |                                                                          |
| Input voltage                              | 3.3 VDC to 5 VDC                                                         |
| Maximum current                            | 400 mA                                                                   |
| Minimum required LNA Gain                  |                                                                          |
|                                            | 32.0 dB                                                                  |
| Environmental characteristics <sup>9</sup> |                                                                          |
| Temperature                                |                                                                          |
| Operating                                  | -40 °C to +75 °C                                                         |
| Storage                                    | -55 °C to +85 °C                                                         |
| Vibration                                  |                                                                          |
|                                            | MIL810F, tailored<br>Random 6.2 gRMS operating<br>Random 8 gRMS survival |
| Mechanical shock                           |                                                                          |
|                                            | MIL810D ±40 g 10ms operating<br>±75 g 6ms survival                       |
| Operating Humidity                         |                                                                          |
|                                            | 5% to 95% R.H. non-condensing, at +60 °C                                 |



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352  
Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

# Trimble BD1092i

Dual antenna receiver module with integrated inertial navigation system

| Positioning specifications <sup>2, 10</sup> No GNSS Outages |                      |                      |                      |                        |                      |                      |                      |                      |
|-------------------------------------------------------------|----------------------|----------------------|----------------------|------------------------|----------------------|----------------------|----------------------|----------------------|
|                                                             | Autonomous           | SBAS <sup>4</sup>    | DGNSS                | RTK                    | INS-Autonomous       | INS-SBAS             | INS-DGNSS            | INS-RTK              |
| <b>Position (m)</b>                                         | 1.00 (H)<br>1.50 (V) | 0.50 (H)<br>0.85 (V) | 0.25 (H)<br>0.50 (V) | 0.008 (H)<br>0.015 (V) | 1.00 (H)<br>1.50 (V) | 0.50 (H)<br>0.85 (V) | 0.40 (H)<br>0.60 (V) | 0.05 (H)<br>0.03 (V) |
| <b>Roll/Pitch (deg)<sup>11</sup></b>                        | 0.10                 | 0.10                 | 0.10                 | 0.10                   | 0.10                 | 0.10                 | 0.10                 | 0.10                 |
| <b>Heading (deg) on 2 m Baseline</b>                        | 0.09                 | 0.09                 | 0.09                 | 0.09                   | 0.09                 | 0.09                 | 0.09                 | 0.09                 |

| Positioning specifications <sup>2, 10</sup> 10 second GNSS Outages |            |                   |       |     |                      |                      |                      |                      |
|--------------------------------------------------------------------|------------|-------------------|-------|-----|----------------------|----------------------|----------------------|----------------------|
|                                                                    | Autonomous | SBAS <sup>4</sup> | DGNSS | RTK | INS-Autonomous       | INS-SBAS             | INS-DGNSS            | INS-RTK              |
| <b>Position (m)</b>                                                | N/A        | N/A               | N/A   | N/A | 1.50 (H)<br>1.80 (V) | 1.20 (H)<br>1.20 (V) | 1.00 (H)<br>1.00 (V) | 0.30 (H)<br>0.20 (V) |
| <b>Roll/Pitch (deg)<sup>11</sup></b>                               | N/A        | N/A               | N/A   | N/A | 0.10                 | 0.10                 | 0.10                 | 0.10                 |
| <b>Heading (deg) on 2 m Baseline</b>                               | N/A        | N/A               | N/A   | N/A | 0.50                 | 0.50                 | 0.50                 | 0.50                 |

- 1 Trimble BD1092i is available in a variety of software configurations. Specifications shown reflect full capability.  
 2 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality. 1 sigma level, when using Trimble Zephyr™ 2/3 antennas, Add 1 ppm for RTK position accuracies.  
 3 At maximum output rate.  
 4 GPS only and depends on SBAS System performance. FAA WAAS accuracy specifications are <5 m 3DRMS.  
 5 Typical observed values.  
 6 No previous satellite (ephemerides / almanac) or position (approximate position or time) information.  
 7 Ephemerides and last used position known.  
 8 Regulated by US State Department International Traffic in Arms Regulations' (ITAR) Munitions List, and the Missile Technology Control Regime (MTCR).  
 9 Dependent on appropriate mounting/enclosure design.  
 10 Detailed specifications are available at [oemgnss.trimble.com](http://oemgnss.trimble.com)  
 11 Pitch and roll available in INS positioning modes. Pitch or roll in non INS modes.

Specifications subject to change without notice.



14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352  
 Fax: +972-3-9243385 | [sales@hypertech.co.il](mailto:sales@hypertech.co.il) | [www.hypertech.co.il](http://www.hypertech.co.il)



© 2026, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo, CenterPoint, ProPoint, RangePoint, Spectrum and Trimble RTX are trademarks of Trimble Inc. or its subsidiaries, registered in the United States and in other countries. CMR+, EVEREST, IonoGuard, JammerGuard, Maxwell and Zephyr are trademarks of Trimble Inc. or its subsidiaries. Galileo is developed under a License of the European Union and the European Space Agency. Google, Google Play, Android and other marks are trademarks of Google LLC. All other trademarks are the property of their respective owners. PN 022520-160 (08/26)