

# RUT901

## INDUSTRIAL CELLULAR ROUTER



RUT901 360° VIEW

// The RUT901 cellular router delivers the top-rated features of its predecessors, the RUT950 and RUT951, to the market.

// The router features dual SIM 4G cellular connectivity and Wi-Fi, as well as 4x Ethernet interfaces, to meet the needs of the many varied IoT solutions.

// The device guarantees high-performance, providing automatic WAN failover to an available backup connection, guaranteeing network continuity and eliminating downtime.

// The RUT901 is dedicated to professional industrial use cases with its high customization possibilities, security features, industrial protocols, and compatibility with Teltonika Networks' Remote Management System (RMS).



### CONNECTIVITY

4G LTE (Cat 4), 3G, 2G

### DUAL SIM

With auto-failover, backup WAN and other switching scenarios

### WI-FI

Wireless Access Point with Hotspot functionality

### FIREWALL & VPNs

Firewall and numerous VPN services, including OpenVPN, IPsec, PPTP, L2TP and DMVPN



# RMS COMPATIBLE WITH RUT901

REMOTE MANAGEMENT SYSTEM

MANAGEMENT

ALERTS

CONFIGURATION

ACCESS

FOTA

# KEY FEATURES

## HARDWARE

Mobile	4G (LTE) – Cat 4 up to 150 Mbps, 3G – Up to 21 Mbps, 2G – Up to 236.8 kbps
CPU	MediaTek, MIPS 24KEc, 580MHz
Storage	16 MB, SPI Flash
Memory	128 MB, DDR2
Powering option	4-pin power socket, 9-30 VDC
SIM	2 x SIM slots (Mini SIM - 2FF), 1.8 V/3 V, external SIM holders, eSIM (Optional)
Antenna connectors	2 x SMA female for LTE, 2 x RP-SMA female for WiFi antenna connectors
Ethernet	4 x RJ45 ports, 10/100 Mbps
Wi-Fi	IEEE 802.11b/g/n, Access Point (AP), Station (STA)
Inputs/Outputs	1 x Digital Input, 1 x Digital Output on 4-pin power connector
Status LEDs	1 x bi-color connection status LED, 5 x connection strength LEDs, 4 x LAN status LEDs, 1 x Power LED
Operating temperature	-40 °C to -75 °C
Housing	Aluminium housing, plastic panels
Dimensions (W x H x D)	110 x 50 x 100 mm
Weight	297 g

## SOFTWARE

Operating system	RutOS (OpenWrt based Linux OS)
Mobile features	SIM switch, Status, SMS, Black/White list, Band management, APN, Bridge, Passthrough
Network protocols	VoIP passthrough support, Connection monitoring, Firewall, DHCP, QoS / Smart Queue Management (SQM), DDNS, Network backup, Load balancing, SSHFS
Network features	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL v3, TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SMPP, SMNP, MQTT, Wake On Lan (WOL)
Security	Authentication, Firewall, Attack prevention, VLAN, Mobile quota control, WEB filter, Access control
Routing	Static routing, Dynamic routing (BGP, OSPF v2, RIP v1/v2, NHRP)
VPN	OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard
Monitoring and management	WEB UI, FOTA, SSH, SMS, Call, TR-069, MQTT, SNMP, JSON-RPC, MODBUS, RMS
Connection monitoring	Ping Reboot, Wget Reboot, Periodic Reboot, LCP and ICMP for link inspection
Cloud solutions	RMS, Cloud of Things, ThingWorx, Cumulocity, Azure IoT Hub
Hotspot	Captive portal (Hotspot), internal/external Radius server, built in customizable landing page
SMS features	SMS status, SMS configuration, send/read SMS via HTTP POST/GET, EMAIL to SMS, SMS to EMAIL, SMS to HTTP, SMS to SMS, scheduled SMS, SMS autoreply, SMPP

### FRONT VIEW

### BACK VIEW

