

# SL900 GNSS Receiver

## Data Specifications

### GNSS

#### Signal Tracking

GPS (L1C/A, L1C, L2C, L2P, L5)  
GLONASS<sup>1</sup> (L1C/A, L2C, L2P, L3, L5)  
BeiDou<sup>2</sup> (B1, B2, B3)  
Galileo<sup>3</sup> (E1, E5AltBOC, E5a, E5b, E6)  
IRNSS (L5)  
QZSS (L1C/A, L1C, L2C, L5, L6)  
SBAS WASS,EGNOS, GAGAN,etc (L1, L5)  
L-Band (Up to 5 Channels) TerraStar®

#### No. of Channels

555

### MEASUREMENT PERFORMANCE

#### Real-time Kinematic

H: 8mm + 1ppm RMS / V: 15mm + 1ppm RMS

#### Network RTK

H: 8mm + 0.5ppm RMS / V: 15mm + 0.5ppm RMS

#### Post Processing Kinematic

H: 8mm + 1ppm RMS / V:15mm + 1ppm RMS

#### High-precision Static

H: 2.5mm + 0.1ppm RMS / V: 3.5mm + 0.4ppm RMS

#### Static and Fast Static

H: 2.5mm + 0.5ppm RMS / V: 5mm + 0.5ppm RMS

#### DGPS Position Accuracy

H: 25cm RMS / V: 50cm RMS

#### SBAS Position Accuracy

H: 50cm RMS / V: 85cm RMS

#### Code Differential

DGPS/RTCM

#### Initializing Time

2-10s

#### Initializing Reliability

99.9%

#### SmartLink (worldwide correction service) optional

Adaptive on-the-fly satellite selection  
Remote precise point positioning (3 cm 2D)<sup>1</sup>,  
Initial convergence to  
full accuracy typically 18 min, Re-convergence < 1 min

#### SmartLink fill (worldwide correction service) optional

Bridging of RTK outages up to 10 min (3 cm 2D)

#### Tilt Survey Performance

Additional horizontal pole-tilt uncertainty typically less than  
10mm +0.7 mm/°tilt (2.5cm accuracy in the inclina-  
-tion of 30° under ideal circumstances)

### COMMUNICATIONS

#### Communication Ports

Internal 4G Mobile Network  
TDD-LTE/FDD-LTE/WCDMA/GPRS/GSM  
GSM 900 MHz &1800 MHz  
WCDMA 2100 MHz/900 MHz  
LTE Band 1,3,7,8,20

Bluetooth: V2.1 + EDR, NFC, E-Bubble  
Wi-Fi: 2.4G , 802.11b/g/n  
USB, TNC antenna port, SIM card slot,  
TF card slot, DC power input (5-pin)  
Internal Radio: Satel radio for Tx/Rx<sup>4</sup>  
Transmitting Power:1 W& 2 W  
Frequency Range:403Mhz-473Mhz  
Working Range: Typically 3~5km, optimal 5~8km

### SYSTEM

#### Operation System

Linux

#### Start-up Time

3s

#### Data Storage

Circulating 16GB Internal Storage;  
Supports 32G SD card

### DATA MANAGEMENT

Output rate 1hz, 2Hz, 5Hz. Anything  
above are extra payable.  
CMR, RTCM2.X, RTCM3.0, RTCM3.2  
GNS, Rinex  
Full NMEA output language with GPGLL/  
GPGLL/GPGSA/GPGSV/GPRMC  
TerraStar® and RTK Assist Service

### GENERAL

#### Environmental

IP67 environmental protection  
Waterproof to 1m (3.28ft) depth  
Temporary Submersion  
Shock resistant body to 2m (6.5ft) pole drop  
Temperature -40°C to 65°C Operating  
-40°C to 85°C Storage

#### Physical Properties

Size: 170mm x 95mm  
Weight: 1.2kg including battery  
Battery: 5,000mAh Lithium-Ion Battery  
Operation Time: 10 hours (RTK Rover)

Note

<sup>1</sup> Hardware ready for L3 and L5

<sup>2</sup> Designed for BeiDou phase 2 and 3, B1 and B2 compatibility, B3 conditionally supported and subject to change.

<sup>3</sup> E1bc support only. Hardware ready for E6bc

<sup>4</sup> Optional: Frequency 865-867 MHz, transmitting power 0.1w-1w adjustable

<sup>5</sup> Optional

**SATLAB**  
GEOSOLUTIONS

# SL900 GNSS Receiver



**HYPER-TECH**  
**Systems**

Made by Sweden

14 Odem ST. P.O.B. 7042 Petach Tikva 4917001, ISRAEL | Office: +972-3-924-3352  
Fax: +972-3-9243385 | sales@hypertech.co.il | www.hypertech.co.il

*The SL900 is a high-precision GNSS receiver that performs even under the most demanding conditions. With its features, the SL900 is capable of delivering highly accurate data in real-time to any devices via a Bluetooth connection. Compact and lightweight, this GNSS receiver is one of the most flexible solutions that promises positioning reliability.*



Tilt compensation solution

With surveyors in mind, Satlab designed a solution to increase efficiency in your workflow by cutting down time wasted from offsetting slanted measurements. With the tilt compensator, the SL900 can save up to 20 percent of time compared to conventional surveying practices. This solution allows you to focus on your surroundings conveniently while ensuring your safety and comfort.



Applications

- Monitoring
- Mapping
- Land Survey
- Topography and As-built
- Landfill
- Hydrographic
- Agriculture
- Sensor
- UAV Base Station

Efficient and dependable

Powered by NovAtel OEM729 GNSS engine, this receiver offers precise positioning and advanced interference mitigation which performs even in the most remote or challenging environments. Using its 555 channel tracking capabilities, it can track all current and upcoming signals, offering sub-metre to centimetre precise positioning with different modes (RTK, PPK, Static).

SmartLink

It can reduce downtime in the field with continuous RTK coverage during correction outages from an RTK base station or VRS network.

Satellite correction service

The SL900 has TerraStar capabilities that use a global network of multi-GNSS reference stations and advanced algorithms to generate highly precise GNSS satellite orbit, clock, biases, and other system parameters. These data allow TerraStar to provide correction services with sub-metre or centimetre-level positioning accuracy to SL900 receivers. Get your corrections transmitted in real-time, with minimal latency via satellites and cellular networks worldwide.

TECHNICAL SUPPORT  
Satlab offers online resources and a professional support network available worldwide.

